

## Specification Sheet - POSlone

**Company:** Pure Vista Ltd  
**Address:** Pendewey  
Stoney Lane  
Bodmin  
Cornwall  
PL31 2QX

**Telephone:** 01208 261040  
**Fax:** 01208 261041  
**Email:** [sales@pure-vista.com](mailto:sales@pure-vista.com)  
**Website:** <http://pure-vista.com>

**Product:** Posi-Glaze Glass Balustrade  
**Materials:** Aluminium channel anodised to min. 20µm (AA25)  
Aluminium top Bead in stainless steel effect anodised to min. 20µm (AA25)  
Aluminium side cladding in stainless steel effect anodised to min. 20µm (AA25)  
Plastic glass clamps for thickness 12mm through to 23mm  
Aluminium clamp bar anodised to 10µm (AA10)  
Trapezoidal bolt 316 Stainless Steel  
Rubber Gasket with Nylon Strip

**Testing:** Meets Local Building Regulations:  
BS 6180:2011 (United Kingdom)  
Avis Technique garde-corps (France)  
AbP DIN 12008-4 (Germany)

**Safety:** When installing glass balustrade high safety requirements must be met to meet the correct criteria, these are only possible when changing some of the system specifications i.e. glass type and thickness, handrail requirement. Reference must be made to the local building Standards to meet these criteria. Please contact your local building control office or us for assistance on what the criteria is.

**Description:** An adjustable balustrade system. Glass is able to tilt allowing for easy alignment for the top of panels. The channels are pre-drilled at 200mm centres.  
A variety of glass thicknesses can be used ranging from 12mm to 21.5mm (+/- tolerances), test reports covering several glass thicknesses are available and must be referred to when specifying.  
Additional items/accessories are available:  
Pre-fabricated corners, joining dowels, end caps, BalconySeal™ Waterproof drain block system.  
Handrail options are also available in aluminium or stainless steel. These are of slot tube design using a rubber gasket to sit on top of the glass.

**Specifying:** All our products are available in CAD/BIM formats. Please find downloads on our website or contact us for CAD files which are required.  
Test certificates are also available online or contact us for specific requirements. We have carried out a vast range of testing at different heights to allow for taller glass panels.

System design loads; 0.36kN, 0.74kN, 1.5kN/m

**Product Ref:** **POSlone Base Mount Channel – Brushed Silver Anodised Aluminium**  
POC-0105 – 1500mm Length  
POC-010 – 3000mm Length  
POC-016 – 6000mm Length

**POSlone Base Mount Channel – Brushed Black Anodised Aluminium**  
POC-0105-BK – 1500mm Length  
POC-030-BK – 3000mm Length

**POSlone Top Seal Strip**  
POS-0105 – 1500mm Length – Brushed Silver Anodised Aluminium  
POA-010 – 3000mm Length – Brushed Silver Anodised Aluminium  
POA-016 – 6000mm Length – Brushed Silver Anodised Aluminium  
POA-0305BK – 1500mm Length – Brushed Black Anodised Aluminium  
POA-010BK – 3000mm Length – Brushed Black Anodised Aluminium

**POSlone – Adjustment Plastic Bead**

POAB-01 – To suit glass thicknesses 12mm – 17.5mm

POAB-02 – To suit glass thickness 19mm

POAB-03 – To suit glass thicknesses 21.5mm – 23mm

**POSlone – Glass Clamp Kits for 3000mm**

POB-0012 – To suit 12mm Toughened Glass

POB-0013 – To suit 12.76mm – 13.52mm Toughened Laminate Glass

POB-0015 – To suit 15mm Toughened Glass

POB-0017 – To suit 16.76mm – 17.52mm Toughened Laminate Glass

POB-0019 – To suit 19mm Toughened Glass

POB-0021 – To suit 20.76mm – 21.52mm Toughened Laminate Glass

POB-0021 – To Suit 20.76mm – 21.52mm Toughened Laminate SentryGlas for 1.5kN Side Fix

**Handrail – Slot Tube - 42.4mm Diameter, 1.5mm wall thickness**

HRA42S-001 – 3000mm Length – Aluminium Silver Brushed AA25

HRA42S-002 – 6000mm Length – Aluminium Silver Brushed AA25

HRA42B-001 – 3000mm Length – Aluminium Black Brushed AA25

HRA42B-002 – 6000mm Length – Aluminium Black Brushed AA25

HR42-001 – 1500mm Length – Stainless Steel 316G Satin

HR42-002 – 3000mm Length – Stainless Steel 316G Satin

HR42-003 – 6000mm Length – Stainless Steel 316G Satin

HR42M-001 – 1500mm Length – Stainless Steel 316G Mirror Polish

HR42M-002 – 3000mm Length – Stainless Steel 316G Mirror Polish

HR42M-003 – 6000mm Length – Stainless Steel 316G Mirror Polish

**Handrail – Gasket for 6000mm**

HR42G-0012 – Gasket Insert for 12mm Glass

HR42G-0015 – Gasket Insert for 15mm-17.52mm Glass

HR42G-0019 – Gasket Insert for 19mm-21.52mm Glass

If you have any questions regarding products, fitment options, required specifications or project queries please contact the team on the above contact details.